

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.

A

B

C

D

E

F

改訂 REV.	変更事項 DESCRIPTIONS	年月日 DATE	0
△			




極数 Cir- cuits	寸法/Dimension	
	A	B
02	-	8.9
03	6.6	12.2
04	9.9	15.5

NOTE

1. 一般公差: $0 < L \leq 3.0: \pm 0.3$ $3.0 < L \leq 9.0: \pm 0.4$ $9.0 < L: \pm 0.5$

NOTE

1. Unless otherwise specified,

tolerances are $0 < L \leq 3.0: \pm 0.3$ $3.0 < L \leq 9.0: \pm 0.4$ $9.0 < L: \pm 0.5$ 

リテーナ RETAINER		PA (GF強化) PA (GF)		UL94V-0, ナチュラル NATURAL	
品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS	
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER	殿
A4	METRIC		MAR.19.2024	品名 PART NAME	HIL コネクタ HIL CONNECTOR
日本圧着端子製造株式会社 J.S.T. MFG.CO., LTD.				形番 PART No.	HILS-()V
				図番 DRAWING No.	KRD-45202-1
					RO

本図面はJST所有の情報であり、書面による許可なく無断で使用、改変、複製または公開する行為を禁止する。
日本語と英語の表現上齟齬又は紛議が生じた時は、日本語が優先する。

COPYRIGHT © 2024 J.S.T. MFG.CO., LTD. EC4121-5

20240325NE387565