


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.




極数 Circuits	寸法 / Dimensions					
	B0	B1	F	S	W	W1
6	16.3	10.5	14.2	28.4	32	33.5
7	18.3	12.5				
8	20.3	14.5				
9	22.3	16.5				
10	24.3	18.5				
11	26.3	20.5	20.2	40.4	44	45.5
12	28.3	22.5				
13	30.3	24.5				
15	34.3	28.5	26.2	52.4	56	57.5


ボス/boss	形番/Part No.
ボス無し without boss	BM () B-PASS-TF (LF) (SN)
ボス付き with boss	BM () B-PASS-1-TF (LF) (SN)

NOTE

- コネクタ本体については、単体の別図面を参照ください。
- 梱包数量：500個/リール。
- リードテープ長さ



4. カバーテープの剥離強度：0.1～1N (剥離速度300mm/分)




5. 材料：キャリアテープ：ポリスチレン (PS)
カバーテープ：ポリエステル (PET)
リール：フランジ部-ポリスチレン (PS)
コア部-ポリプロピレン (PP)
ポリスチレン (PS)


6. 一般公差：±0.3

NOTE

- Connector part: See the DWG. of PA Connector.
- Quantity to be packaged: 500 pcs/reel
- Leading tape length.



4. Cover tape peel strength: 0.1~1N
(Peel speed: 300mm/minute)



5. Material: Carrier tape; Polystyrene (PS)
Cover tape; Polyester (PET)
Reel; Flange; Polystyrene (PS)
Core; Polypropylene (PP)
Polystyrene (PS)

6. Unless otherwise specified,
tolerances are ±0.3

品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER
A2	METRIC	第1角法 1st Angle	FEB. 19, 2024	品名 SERIES NAME
JST 日本圧着端子製造株式会社 J.S.T. MFG. CO., LTD.				形番 PART No.
KRD-46626-1				図番 DRAWING No.
RO				

