


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.




極数 Circuits	形番 Part No.	A	B
4	04MQ-BT	6.0	10.0
5	05MQ-BT	8.0	12.0
6	06MQ-BT	10.0	14.0
7	07MQ-BT	12.0	16.0
8	08MQ-BT	14.0	18.0
9	09MQ-BT	16.0	20.0
10	10MQ-BT	18.0	22.0
12	12MQ-BT	22.0	26.0

NOTE

- 1. 指定公差: ± 0.3
- 2. 基板の穴ピッチの公差は累積しないこと。

NOTE

- 1. Unless otherwise specified, tolerances are ± 0.3
- 2. Tolerance of hole pitch on PCB are not cumulative.



推奨基板穴寸法 (コネクタ装着側から見た図)
Recommendable P.C.Board hole layout
(The figure viewed from connector mounting side.)

2	ソケットハウジング SOCKET HOUSING	PA		UL94V-0	ナチュラル NATURAL
1	コンタクト CONTACT	銅合金 COPPER ALLOY	すずめっき TIN-PLATED		
品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS	
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER	殿
A3	METRIC		JUN.14.2024	品名 SERIES NAME	MQ コネクタ MQ CONNECTOR
日本圧着端子製造株式会社 J.S.T. MFG.CO.,LTD.				形番 PART No.	()MQ-BT
				図番 DRAWING No.	KRD-05783-6
					R0