

1000AAC/DC current measurements

1400VDC volt measurements

TRMS measurements

Resistance measurement to 10,000Ω

Continuity with beeper below 35Ω

Frequency measurements from V and A

Hold function to "freeze" readings

Designed to measure Amps and Volts at the same time

Push-button for easy ADC zeroing

Large easy-to-read 9999-count display

Includes test leads and soft carrying case

F05é³á½çèì™

ã°§ã“□æ□□è¿°í¼š

Compact handheld size, ultra practical and ergonomic design

TRMS measurement

Crest factor of 3.5 at 600Arms and 900Vrms

Peak function enables the capture of 500<μ>s crest values

Min/Max automatic capture of peak values at 100ms

Continuity at programmable threshold from 1 to 40W

Selectable V-Live™ function (buzzer warning of voltage >45V peak, considered to be hazardous)

Battery life displayed directly in hours

Automatically detects AC or DC and is auto-ranging

Automatic DC current zeroing

Backlit Digital Display

EN 61010-1, EN 61010-2-032, 600V Cat. III

Supplied with test leads and a soft carrying case

AEMCCM605é³á½çèì™

F07é'³â½çèj™

10,000-count LCD Display - Excellent Resolution

100AAC/DC Ammeter with low 10A Range (1mA Resolution)

Tapered Jaws for crowded wiring or areas (Ø .45" â€“ 12mm Jaw Opening)

600VAC/DC Voltmeter

Analog Output in AAC/DC A

Auto-Ranging & ADC Zero Push-button

Data HOLD & PEAK functions

Relative Function to compare two measurements

Ohm Range & Continuity Test with Beeper, 600V Protection

Batteries: AUTO-OFF and Low Battery Indicator

IEC/EN 61010 Safety Rated & CE Mark

F07é'³â½çèj™

â°§â““□æ□□èç°T/š

Compact handheld size, ultra practical and ergonomic design

TRMS measurement

Crest factor of 3.5 at 600Arms and 900Vrms

Peak function enables the capture of 500<µ>s crest values

Min/Max automatic capture of peak values at 100ms

Continuity at programmable threshold from 1 to 40W

Selectable V-Live™ function (buzzer warning of voltage >45V peak, considered to be hazardous)

Battery life displayed directly in hours

Automatically detects AC or DC and is auto-ranging

Automatic DC current zeroing

Backlit Digital Display

EN 61010-1, EN 61010-2-032, 600V Cat. III

Supplied with test leads and a soft carrying case

