



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.

A
B
C
D
E

1 2 3 4 5 6 7 8

改訂 REV.	変更事項 DESCRIPTIONS	年月日 DATE	0
△			

- NOTE
1. 指定公差: ± 0.5
2. 基板の穴ピッチの公差は累積しないこと。
- NOTE
1. Unless otherwise specified, tolerances are: ± 0.5
2. Tolerance of hole pitch on PCB are not cumulative.



基板穴参考寸法 (コネクタ装着側より見る)
Recommended P.C.Board Layout
(View of component side)

キーイングNo. Keying No.	キーイング形状 Configuration of keying	形番 Part No.	色 Color
X		BC04B-JFPSE-GHXS	青 Blue
Y		BC04B-JFPSK-GHYS	黒 Black

3	補強タブ REINFORCEMENT	銅合金 COPPER ALLOY	すずめっき TIN PLATED	
2	タブコンタクト TAB CONTACT	銅 COPPER	部分金めっき SELECTIVE GOLD PLATED	
1	ヘッダーハウジング HEADER HOUSING	PA (GF強化) PA (GF)		
品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER
A3	METRIC		MAY.15.2024	品名 SERIES NAME
日本圧着端子製造株式会社 J.S.T. MFG.CO.,LTD.				JFPS コネクタ
				JFPS CONNECTOR
				形番 PART No.
				BC04B-JFPS () -GH () S
				図番 DRAWING No.
				KRD-55523
				R0