



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR ADAPTED, COPIED, OR PUBLISHED WITHOUT WRITTEN PERMISSION. IN THE EVENT THAT THERE ARISE ANY DOUBTS OR CONTROVERSIES BETWEEN JAPANESE AND ENGLISH EXPRESSION, THE JAPANESE TEXT SHALL PREVAIL.



- NOTE
- 1. 指定公差: ±0.3
 - 2. JSTマーク側を回路No.1とする。
 - 3. 基板の穴ピッチの公差は累積しないこと。
- NOTE
- 1. Unless otherwise specified, tolerances are ±0.3
 - 2. Circuit No.1 on JST mark side.
 - 3. Tolerance of hole pitch on PCB are not cumulative.

3	ソケットハウジング SOCKET HOUSING	PA (GF強化) PA (GF)		UL94V-0	ナチュラル Natural
2	コンタクト CONTACT	銅合金 COPPER ALLOY	すずめっき TIN-PLATED		
1	コンタクト CONTACT	銅合金 COPPER ALLOY	すずめっき TIN-PLATED		
品番 No.	部品名 PART NAME	材質 MATERIAL	処理 SURFACE FINISH	備考 REMARKS	
サイズ SIZE	単位 UNIT	投影法 PROJECTION	作図年月日 DATE	納入先 CUSTOMER	殿
A3	METRIC		MAR.19.2024	品名 SERIES NAME	JE コネクタ JE CONNECTOR
日本圧着端子製造株式会社 J.S.T.MFG.CO., LTD.				形番 PART No.	() R-JE (LF) (SN)
				図番 DRAWING No.	KRD-38394-2
					R0