

RESISTOR BUILT-IN TYPE PNP TRANSISTOR

FEATURES

- Compact package
- Resistors built-in type
- Complementary to FA4xxx

ORDERING INFORMATION

PART NUMBER	PACKAGE
FN4xxx	SC-59

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

Collector to Base Voltage	V_{CBO}	-60	V
Collector to Emitter Voltage	V_{CEO}	-50	V
<R> Emitter to Base Voltage	V_{EBO}	Note1	V
Collector Current (DC)	I_C	-0.1	A
Collector Current (pulse)	$I_{C(pulse)}$	-0.2	A
Total Power Dissipation	P_T	0.2	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

<R> Note 1.


PART NUMBER	V_{EBO} (V)	MARK	R_1 (k Ω)	R_2 (k Ω)
FN4A4M	-10	NA1	10.0	10.0
FN4F4M	-10	NB1	22.0	22.0
FN4L4M	-10	NC1	47.0	47.0
FN4L3M	-10	ND1	4.7	4.7
FN4L3N	-5	NE1	4.7	10.0
FN4L3Z	-5	NF1	4.7	
FN4A3Q	-5	NG1	1.0	10.0
FN4A4P	-5	NH1	10.0	47.0
FN4F4N	-5	NJ1	22.0	47.0

Note 2. $PW \leq 10$ ms, Duty Cycle $\leq 50\%$


The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.

Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.

PACKAGE DRAWING (Unit: mm)



EQUIVALENT CIRCUIT



PIN CONNECTION

- 1: Emitter
2: Base
3: Collector

PART NUMBER	V_{EBO} (V)	MARK	R_1 (k Ω)	R_2 (k Ω)
FN4L4L	-15	NK1	47.0	22.0
FN4A4Z	-5	NL1	10.0	
FN4F4Z	-5	NM1	22.0	
FN4L4Z	-5	NN1	47.0	
FN4F3M	-10	NP1	2.2	2.2
FN4F3P	-5	NQ1	2.2	10.0
FN4F3R	-5	NR1	2.2	47.0
FN4A4L	-15	NS1	10.0	4.7
FN4L4K	-25	NT1	47.0	10.0

ELECTRICAL CHARACTERISTICS (T_A = 25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I _{CBO}	V _{CB} = -50 V, I _E = 0			-100	nA
DC Current Gain	h _{FE1}	V _{CE} = -5.0 V, I _C = -5.0 mA	Note1			-
	h _{FE2}	V _{CE} = -5.0 V, I _C = -50 mA				-
Collector Saturation Voltage	V _{CE(sat)}	I _C = -5.0 mA, I _B = -0.25 mA			-0.2	V
Low-level Input Voltage	V _{IL}	V _{CE} = -5.0 V, I _C = -100 μA	Note2			V
High-level Input Voltage	V _{IH}	V _{CE} = -0.2 V, I _C = -5.0 mA				V
Input Resistor	R _I		Note3			kΩ
Emitter to Base Resistor	R _E					kΩ

Note 1.


PART NUMBER	h _{FE1}			h _{FE2}			UNIT
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
FN4A4M	35		100	80			-
FN4F4M	60		195	90			-
FN4L4M	85		340	95			-
FN4L3M	20		80	80			-
FN4L3N	35		100	80			-
FN4L3Z	135		600	100			-
FN4A3Q	35		100	80			-
FN4A4P	85		340	95			-
FN4F4N	85		340	95			-
FN4L4L	60		195	90			-
FN4A4Z	135		600	100			-
FN4F4Z	135		600	100			-
FN4L4Z	135		600	100			-
FN4F3M	8		50	50			-
FN4F3P	35		100	80			-
FN4F3R	85		340	95			-
FN4A4L	20		80	80			-
FN4L4K	35		100	80			-

Note 2.

PART NUMBER	V _{IL}			V _{IH}			UNIT
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
FN4A4M			-0.8	-3.0			V
FN4F4M			-0.8	-4.0			V
FN4L4M			-0.8	-5.0			V
FN4L3M			-0.8	-3.0			V
FN4L3N			-0.6	-3.0			V
FN4L3Z			-0.5	-1.2			V
FN4A3Q			-0.5	-2.0			V
FN4A4P			-0.5	-3.0			V
FN4F4N			-0.6	-3.0			V
FN4L4L			-0.9	-6.0			V
FN4A4Z			-0.5	-2.0			V
FN4F4Z			-0.5	-3.0			V
FN4L4Z			-0.5	-4.0			V
FN4F3M			-0.8	-3.0			V
FN4F3P			-0.5	-2.0			V
FN4F3R			-0.5	-2.0			V
FN4A4L			-0.9	-6.0			V
FN4L4K			-2.0	-8.0			V








Note 3.

PART NUMBER	R ₁			R ₂			UNIT
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
FN4A4M	7.00	10.00	13.00	7.00	10.00	13.00	kΩ
FN4F4M	15.40	22.00	28.60	15.40	22.00	28.60	kΩ
FN4L4M	32.90	47.00	61.10	32.90	47.00	61.10	kΩ
FN4L3M	3.29	4.70	6.11	3.29	4.70	6.11	kΩ
FN4L3N	3.29	4.70	6.11	7.00	10.00	13.00	kΩ
FN4L3Z	3.29	4.70	6.11				kΩ
FN4A3Q	0.70	1.00	1.30	7.00	10.00	13.00	kΩ
FN4A4P	7.00	10.00	13.00	32.90	47.00	61.10	kΩ
FN4F4N	15.40	22.00	28.60	32.90	47.00	61.10	kΩ
FN4L4L	32.90	47.00	61.10	15.40	22.00	28.60	kΩ
FN4A4Z	7.00	10.00	13.00				kΩ
FN4F4Z	15.40	22.00	28.60				kΩ
FN4L4Z	32.90	47.00	61.10				kΩ
FN4F3M	1.54	2.20	2.86	1.54	2.20	2.86	kΩ
FN4F3P	1.54	2.20	2.86	7.00	10.00	13.00	kΩ
FN4F3R	1.54	2.20	2.86	32.90	47.00	61.10	kΩ
FN4A4L	7.00	10.00	13.00	3.29	4.70	6.11	kΩ
FN4L4K	32.90	47.00	61.10	7.00	10.00	13.00	kΩ





[FN4A4M]



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)




[FN4F4M]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)COLLECTOR CURRENT vs.
COLLECTOR TO EMITTER VOLTAGECOLLECTOR TO EMITTER VOLTAGE vs.
COLLECTOR CURRENT


DC CURRENT GAIN vs. COLLECTOR CURRENT

COLLECTOR SATURATION VOLTAGE vs.
COLLECTOR CURRENT


INPUT VOLTAGE vs. COLLECTOR CURRENT



COLLECTOR CURRENT vs. INPUT VOLTAGE










RESISTOR vs. AMBIENT TEMPERATURE



[FN4L4M]


TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)




[FN4L3M]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)


COLLECTOR CURRENT vs.
COLLECTOR TO EMITTER VOLTAGE




COLLECTOR TO EMITTER VOLTAGE vs.
COLLECTOR CURRENT




DC CURRENT GAIN vs. COLLECTOR CURRENT




COLLECTOR SATURATION VOLTAGE vs.
COLLECTOR CURRENT




INPUT VOLTAGE vs. COLLECTOR CURRENT



COLLECTOR CURRENT vs. INPUT VOLTAGE










RESISTOR vs. AMBIENT TEMPERATURE



[FN4L3N]








TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)



原创力文档
max.book118.com
预览与源文档一致, 下载高清无水印








[FN4L3Z]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4A3Q]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)




[FN4A4P]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)


[FN4F4N]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)


COLLECTOR CURRENT vs.
COLLECTOR TO EMITTER VOLTAGE




COLLECTOR TO EMITTER VOLTAGE vs.
COLLECTOR CURRENT




DC CURRENT GAIN vs. COLLECTOR CURRENT




COLLECTOR SATURATION VOLTAGE vs.
COLLECTOR CURRENT




INPUT VOLTAGE vs. COLLECTOR CURRENT



COLLECTOR CURRENT vs. INPUT VOLTAGE




RESISTOR vs. AMBIENT TEMPERATURE




[FN4L4L]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)


COLLECTOR CURRENT vs.
COLLECTOR TO EMITTER VOLTAGE




COLLECTOR TO EMITTER VOLTAGE vs.
COLLECTOR CURRENT




DC CURRENT GAIN vs. COLLECTOR CURRENT




COLLECTOR SATURATION VOLTAGE vs.
COLLECTOR CURRENT




INPUT VOLTAGE vs. COLLECTOR CURRENT










COLLECTOR CURRENT vs. INPUT VOLTAGE



RESISTOR vs. AMBIENT TEMPERATURE










[FN4A4Z]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)








[FN4F4Z]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4L4Z]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4F3M]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4F3P]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4F3R]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)










[FN4A4L]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)



[FN4L4K]

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)



- **The information in this document is current as of December, 2005. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).