







A
B
C
D
E
F



RECOMMENDED METAL MASK THICKNESS : t=0.15


	COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE		COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE
△						. . .	△						. . .
△						. . .	△						. . .
△						. . .	△						. . .

RECOMMENDED FPC/FFC(S=N/S)



STIFFENER SIDE

- NOTE 1 LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE 0.1 MAX.
2 TO BE DELIVERED WITH TAPE AND REEL PACKAGES.

			4	PHOSPHOR BRONZE	TIN PLATING 1um MIN,OVER NICKEL 1um MIN.			
2	LCP	BLACK	UL94V-0	3	PHOSPHOR BRONZE	(CONTACT AREA)GOLD PLATING,OVER NICKEL 1um MIN. (LEAD AREA)GOLD PLATING,OVER NICKEL 1um MIN. (OTHER) NICKEL PLATING 1um MIN.		
1	LCP	BEIGE	UL94V-0					
NO.	MATERIAL	FINISH,REMARKS		NO.	MATERIAL	FINISH,REMARKS		
CODE NO. (OLD)			DRAWN	DESINGED	CHECKED	APPROVED	RELEASED	
			D.H,CHO	D.H,CHO	D.H,CHO	H.C,SONG	ENG 17.08.31 DEPT	
			17. 04 . 10	17. 04 . 10	17. 04 . 10	17. 04 . 10		
	DRAWING NO.			PART NO.				
SCALE 4 : 1	EDC3-632316-80			TF06L-**-S-0.5SH(800)				
UNITS mm	 HIROSE KOREA CO.,LTD.			CODE NO.			1/3	
			CL *****-800					

Oct.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window

A


B

C

D

E

F



	COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE		COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE
△						. .	△						. .
△						. .	△						. .
△						. .	△						. .

A


B

C

D

E

F



NOTE 1 . 1 REEL CONTAINS 2,000 PCS.

2	PET	COVER TAPE	4	PS	REEL
1	PET	EMBOSS TAPE	3	CONNECTOR	CONNECTOR
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
CODE NO. (OLD)			DRAWN	DESINGED	CHECKED
			D.H,CHO	D.H,CHO	D.H,CHO
			17. 04 . 10	17. 04 . 10	17. 04 . 10
			APPROVED	RELEASED	
			H.C, SONG		ENG 17.08.31 DEPT
DRAWING NO. EDC3-632316-80			PART NO. TF06L-**-S-0.5SH(800)		
SCALE 2 : 1			CODE NO. CL *****-800		
UNITS mm			2/3		

Oct.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window

A

B

C

D

E

F

A

B

C


D

E

F

	COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE		COUNT	DISCRIPTION OF REVISIONS	B	Y	CHKD	DATE
△						. .	△						. .
△						. .	△						. .
△						. .	△						. .

PART NUMBER	NUMBER OF CONTACTS	CONNECTOR, FPF/FFC, PCB, METAL MASK DIMENSION										PACKING DIMENSION			
		A	B	C	D	E	F	G	H	I	J	K	L	M	N
TF06L-50S-0.5SH(800)	50S	24.5	25.55	27.66	29.88	30.3	27	25.5	27.2	27.3	0.15	20.2	40.4	44	44.5
TF06L-60S-0.5SH(800)	60S	29.5	30.55	32.66	34.88	35.3	32	30.5	32.2	32.3	0.15	26.2	52.4	56	56.5
TF06L-68S-0.5SH(800)	68S	33.5	34.55	36.66	38.88	39.3	36	34.5	36.2	36.3	0.18	26.2	52.4	56	56.5
TF06L-80S-0.5SH(800)	80S	39.5	40.55	42.66	44.88	45.3	42	40.5	42.2	42.3	0.18	26.2	52.4	56	56.5

NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS	
CODE NO. (OLD)			DRAWN	DESINGED	CHECKED	APPROVED	RELEASED
			D.H,CHO	D.H,CHO	D.H,CHO	H.C,SONG	ENG 17.08.31 DEPT
			17. 04 . 10	17. 04 . 10	17. 04 . 10	17. 04 . 10	
		DRAWING NO.		PART NO.			
SCALE N : S		EDC3-632316-80		TF06L-***S-0.5SH(800)			
UNITS mm		HRS HIROSE KOREA CO.,LTD.		CODE NO.			3/3
				CL *****-**-800			

12345678

12345678