

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC
J

DIST

REVISIONS
変更

P
LTR

DESCRIPTION

DATE

DWN

APVD

E

REVISED PER-ECR-20-011859

21AUG2020

M. J

E. I

CAVITY MARK
(ALPHABET:CAPITAL LETTER)

CIRCUIT NO

COMPANY LOGO

SERIES CODE

KEYING: X

ROW ID

SCALE 1:1

2.5Xn=A

2.5

3.3

01 6 8 3 2 1

D

C

B

A

20POS(X-KEY): 1-1827864-0

11.3

8.6

9.4

12.45

9

2.5Xn=A

2.5

3.3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差 ±0.3, ±5°

0-PLC ±

1-PLC ±

2-PLC ±

3-PLC ±

4-PLC ±

ANGLES ±

FINISH
仕上

MATERIAL
材料

DWN
T. KUDO 23AUG2005

CHK
D. MITSUGI 23AUG2005

APVD
D. MITSUGI 23AUG2005

PRODUCT SPEC
製品規格
108-78268, 78298

APPLICATION SPEC
取付適用規格
114-5377

WEIGHT

CUSTOMER DRAWING

DYNAMIC DI200D 2.5mm PITCH
REC HSG
4-20 POS

SIZE
A3

CAGE CODE
00779

DRAWING NO
C-1827864

RESTRICTED TO

SCALE
尺度 4:1

SHEET
1

OF
4

REV
E

1. MATERIAL: GLASS FILLED THERMO PLASTIC
POLYESTER(94V-0), COLOR: BLACK

2. THE SHAPE, SIZE AND POSITION
OF THE CHARACTER SHOW THE OUTLINE.
THEY DON'T SHOW DETAILS.

3. THE KEYING ARRANGEMENT OF "Y" IS
SYMMETRIC WITH "X".

4. DIFFERENT HEIGHT OF LOCK PROTECTOR.
A FINGERTIP IS STOOD AND PUSHED
WHEN OPERATING A LOCK LEVER.

1. 材料: ガラス入り熱可塑性ポリエステル樹脂(94V-0), 色: 黒

2. 文字の形状、大きさ、および位置については、大略を示すものであり、
詳細を示すものではありません。

3. Y KEY形状は、X KEY形状と左右対称

4. LOCK PROTECTORの高さ違いです。
ロックレバー操作の際には、指先を立てて押してください。

20	Y	9	22.5	25.9	27.6	8.3	2-1827864-0
20	X	9	22.5	25.9	27.6	8.3	1-1827864-0
16	Y	7	17.5	20.9	22.6	8.3	2-1827864-8
16	X	7	17.5	20.9	22.6	8.3	1-1827864-8
12	Y	5	12.5	15.9	17.6	8.3	2-1827864-6
12	X	5	12.5	15.9	17.6	8.3	1-1827864-6
12	X	5	12.5	15.9	17.6	8.3	9-1827864-6
10	Y	4	10.0	13.4	15.1	3.3	2-1827864-5
10	X	4	10.0	13.4	15.1	3.3	1-1827864-5
8	Y	3	7.5	10.9	12.6	3.3	2-1827864-4
8	X	3	7.5	10.9	12.6	3.3	1-1827864-4
6	Y	2	5.0	8.4	10.1	3.3	2-1827864-3
6	X	2	5.0	8.4	10.1	3.3	1-1827864-3
6	X	2	5.0	8.4	10.1	3.3	9-1827864-3
4	Y	1	2.5	5.9	7.6	3.1	2-1827864-2
4	X	1	2.5	5.9	7.6	3.1	1-1827864-2
4	X	1	2.5	5.9	7.6	3.1	9-1827864-2
POS	KEY	n	A	B	C	D	PART NO

1470-19 (3/11)

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT -

ALL RIGHTS RESERVED.

LOC
J

DIST

P

LTR

REVISIONS

変更

DESCRIPTION

















DATE

DWN

APVD

SEE SHEET 1

CAVITY MARK
ONLY 4POS



4POS(X-KEY)
1-1827864-2

6POS(X-KEY)
1-1827864-3


8POS(X-KEY)
1-1827864-4

10POS(X-KEY): 1-1827864-5 12POS(X-KEY): 1-1827864-6

4 12POS(X-KEY): 9-1827864-6

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 概
mm



MATERIAL
材料

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差
0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±
4 PLC ±
ANGLES ±

FINISH
仕上

DWN 23AUG2005

CHK T. KUDO

APVD D. MITSUGI

PRODUCT SPEC

製品規格

108-78268, 78298

APPLICATION SPEC

取付適用規格

114-5377

WEIGHT

CUSTOMER DRAWING



TE Connectivity

DYNAMIC DI200D 2.5mm PITCH
REC HSG
4-20 POS

NAME
名称

SIZE

CAGE CODE

DRAWING NO

番号

RESTRICTED TO

SCALE

尺度

SHEET

2

OF

4

REV

E

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT -

ALL RIGHTS RESERVED.

LOC
J

DIST

REVISIONS
変更

P

LTR





DESCRIPTION

DATE




DWN

APVD

SEE SHEET 1




16POS(X-KEY): 1-1827864-8



6POS(X-KEY): 9-1827864-3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm



MATERIAL
材料

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

FINISH
仕上

±

±

±

±

±

±

±

DWN 23AUG2005

CHK T.KUDO

D.MITSUGI 23AUG2005

APVD D.MITSUGI 23AUG2005

PRODUCT SPEC

製品規格

108-78268,78298

APPLICATION SPEC

取付適用規格

114-5377

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME
名称
DYNAMIC D1200D 2.5mm PITCH
REC HSG
4-20 POS

SIZE

CAGE CODE

DRAWING NO

A3

00779

C=1827864

RESTRICTED TO

SCALE

尺度

4:1

SHEET






3

OF

4

REV

E



4 4POS(X-KEY):9-1827864-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

MATERIAL
材料

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差

0 PLC ±

1 PLC ±

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±

FINISH
仕上

DWN
T. KUDO 23AUG2005

CHK
D. MITSUGI 23AUG2005

APVD
D. MITSUGI 23AUG2005

PRODUCT SPEC
製品規格
108-78268, 78298

APPLICATION SPEC
取付適用規格
114-5377

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME
名称
DYNAMIC D1200D 2.5mm PITCH
REC HSG
4-20 POS

SIZE
A3

CAGE CODE
00779

DRAWING NO
番号
C-1827864

RESTRICTED TO

SCALE
尺度
4:1

SHEET
4 OF 4

REV
E

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1827864-4](#)