



Power Cord Splitter, C14 to 2xC13 PDU Style - 10A, 250V, 18 AWG, 18-in. (45.72 cm), Black

MODEL NUMBER: P004-18N-2C13











C14-to-C13 splitter allows 2 devices with C14 inlets to share one AC power input cord and one C13 outlet on a PDU or UPS system.

Features

C14-to-C13 Y-Style Splitter Cord Connects 2 Devices with C14 Inlets to One C13 Outlet This ULlisted IEC-320-C14 to IEC-320-C13 splitter allows two devices with C14 power inlets to share one AC input cord and one C13 outlet. This C14 male to C13 female cord features a C14 end for connecting to an AC power source on a PDU, surge protector or UPS system and two C13 ends for connecting to devices. By connecting two devices to one outlet in your home office or workspace, the power cord splitter frees up space in a PDU or surge protector and helps reduce cable clutter. The length of the C14 connector to the split is 6" and the length of the two C13 connectors is 12" from the split.

IEC Cable Powers a Wide Variety of Essential ElectronicsWith this PC power splitter, a single C13 outlet can power two devices, such as computers, monitors, printers, instrument amplifiers and other equipment compatible with a C13 connector. Ideal for areas where AC outlets are limited, such as rack cabinets, this IEC cable is compatible with power and extension cords.

Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering multiple computers, monitors or other compatible peripherals
- C14 end connects to PDU or UPS power; C13 ends connect to devices' C14 inlets
- C13-to-C14 PDU-style extension cord is ideal replacement for worn-out or missing cable

Applications

- Connect 2 devices like computers, monitors, scanners and printers to one power outlet in your home office, work space or dorm room
- Cut cable clutter by powering up to 2 monitors in a multi-monitor display mount with a single cord
- Save space in a 0U vertical rack-mount PDU by plugging 2 rack devices into one outlet

Package Includes

 P004-18N-2C13 C14 Male to C13 Female Splitter, PDU Style, 18 in., Black

Specifications

| OVERWINE AND THE PROPERTY OF T | | |
|--|--|--|
| OVERVIEW | | |
| UPC Code | 037332213945 | |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Scanner; UPS; PDU | |
| Country/Region | Global | |
| | | |
| INPUT | | |
| Maximum Input Amps | 10 | |
| Voltage Compatibility (VAC) | 100-250 | |
| | | |
| CONNECTIONS | | |





| Side A - Connector 1 | IEC-320-C14 | |
|-------------------------------------|-------------------------------------|--|
| Side B - Connector 1 | (2) IEC-320-C13 | |
| PHYSICAL | | |
| Plug Color | Black | |
| Cable Jacket Color | Black | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | VW-1 | |
| Power Cord Jacket Type | SJT | |
| Cable Outer Diameter (OD) | 7.8mm | |
| Number of Conductors | 3 | |
| Wire Gauge (AWG) | 18 | |
| Wire Gauge (OD - mm²) | 0.82 | |
| Cable Length (ft.) | 1.5 | |
| Cable Length (m) | 0.46 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Operating Humidity Range | 10% to 65% RH | |
| Storage Humidity Range | 10% to 65% RH | |
| FEATURES & SPECIFICATIONS | | |
| Antibacterial | No | |
| Angled Plug | No | |
| High Voltage | Yes | |
| Locking Plug | No | |
| Coiled Power Cord | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | CSA (Canada); cUL Listed; UL Listed | |
| Product Compliance | RoHS; REACH | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.