

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13; GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black	
Model No. Power Cord		
Part No./Ordering No. 208IN4272M5701(R)		Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification
ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>
Prop 65 Statement: <https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.
Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.
A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13;, GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black		
	Model No. Power Cord		
	Part No./Ordering No. 208IN4272M5701(R)		Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

REVISION HISTORY


REV	DESCRIPTION	SUB	DATE	APPROVED
B1	Correct cable rating from 500V to 450/750V	bsiep	12/16/2021	QA
B	Add cordset drawing; revise conductor colors from BRN/BLU/GN-YEL to RED/BLK/GN-YEL; Clarify markings on C13 connector	bsiep	12/03/2020	QA
A	Initial Release	bsiep	05/02/2019	QA

Cordset Information:
CordsetColor:GlobTek Black
Cord Length (mm):2500 +/- 50

NOTES:


GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13; GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 208IN4272M5701(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE





GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13; GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 208IN4272M5701(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13; GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 208IN4272M5701(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A Code:208IN Description:IS 1293:2005 Three Prong India BIS Plug 16A Max Rating (V):250 Rating (A):16.0 Gender:Male Overmolded:Yes	Cable Code:427YY (India Only) Description:GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS Color:GlobTek Black Wire Gauge(AWG):1.0mmsq Cond:3 Type:YY Temp -10° +70° Temperature:70°° C Amps:10 Volts:450/750 OD:7.1 ConductorsColors:RED / BLK / GRN-YEL	End B Code:701-IN Description:IEC320-C13; Rating (V):250 Rating (A):10.0 Gender:Female Overmolded:Yes
Overall cable rating:10A / 250VAC		
Plug Approvals	Cable Approvals	Connector Approvals
 INDIA BIS (cordsets)	 INDIA BIS (cordsets)	No safety logo required for IEC connectors in India ISI (IEC connector for India)
AGENCY ONLINE DOCUMENTS	http://en.globtek.com/cordsets/	
RoHS/RoHS3 Declaration	https://www.globtek.com/pdf/rohs_cert/01t0c000009EMkyAAG	
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf	
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf	
Prop 65 Statement	https://en.globtek.com/prop-65-statement.pdf	
CE.UKCA.Cord	https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01t0c000009EMky	
IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.		

PROPRIETARY INFORMATION


PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2019 - 2025

quest /03/28/2025 7:21:58 AM CLONED FROM 2084272M5701(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: IS 1293:2005 Three Prong India BIS Plug 16A Max to IEC320-C13;, GT Cable #427YY (India Only): 1.0mmsq / 3 Conductors, 7.1mm OD, YY Temp -10° +70°, 70° Deg.C, 450/750V, RED / BLK / GRN-YEL, Approvals: BIS, 2500 +/- 50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 208IN4272M5701(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:200
Description:200 +/- 20mm
Image:



Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):