# molex

Part Number: 22552462

Product Description: 2.54mm Pitch SL Crimp Housing, Dual Row, Version B, Polarized, 46 Circuits, Black

Series Number: 70450

Status: Active

**Product Category:** Connector Housings

Engineering Number: 70450-0071



#### **Documents & Resources**

#### **Drawings**

022552462\_sd.pdf PK-70450-100-001.pdf

#### 3D Models and Design Files

022552462\_stp.zip

#### **Specifications**

PS-70058-001.pdf

PS-70400-001.pdf

TS-70058-001-001.pdf

# **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2024)7663-DC<br>(21 Jan 2025) |
| EU RoHS            | Compliant per EU 2015/863                         |

# Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC

#### - Low-Halogen

# Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

#### General

| Status       | Active  |
|--------------|---|
| Category     | Connector Housings  |
| Series       | 70450   |
| Description  | 2.54mm Pitch SL Crimp Housing,<br>Dual Row, Version B, Polarized, 46<br>Circuits, Black |
| Application  | Signal, Wire-to-Board   |
| Comments     | Version B   |
| Product Name | SL  |
| UPC          | 800753778719  |

# Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

# Physical

| Breakaway          | No         |
|--------------------|------------|
| Circuits (maximum) | 46         |
| Color - Resin      | Black      |
| Flammability       | 94V-0      |
| Gender             | Receptacle |
| Glow-Wire Capable  | No         |
| Material - Resin   | Polyester  |
| Net Weight         | 3.940/g    |
| Number of Rows     | 2          |

| Packaging Type                | Bag            |
|-------------------------------|----------------|
| Panel Mount                   | No             |
| Pitch - Mating Interface      | 2.54mm         |
| Stackable                     | No             |
| Temperature Range - Operating | -40° to +105°C |

## Mates With / Use With

# Mates with Part(s)

| Description  | Part Number  |
|--|--------------|
| C-Grid Right-Angle Dual Row<br>Headers               | <u>70229</u> |
| C-Grid Right-Angle, Dual Row, Low<br>Profile Headers | 70247        |
| C-Grid Vertical Dual Row<br>Breakaway Headers        | 70280        |
| C-Grid Vertical, Dual Row, Low<br>Profile Headers    | 70246        |

# Use with Part(s)

| Description         | Part Number |
|---------------------|-------------|
| SL Female Terminals | 70058       |
| SL Female Terminals | 71851       |

This document was generated on Apr 14, 2025