



4-40 THREADED INSERTS	NO	А	206425-5	
.150±.003	YES	Α	206425-3	
.150±.003	NO	В	206425-2	
.150±.003	NO	А	206425-1	
C	PERIPHERAL SEAL	SEE DETAIL	PART NUMBER	

REVISIONS

DESCRIPTION

DATE DWN APVD

280CT2021 RK MZ

	THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 06/01/94 M.BINNER CHK 6-23-94 R.STONE		TE Connectivi				
	DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME					
	INCHES	OTHERWISE SPECIFIED:	_	INAME	RECEPTACLE	RECEPTACLE HOUSING, REVERSE			
		0 PLC ± - 1 PLC ± - 2 PLC ± .005	PRODUCT SPEC 108-10024	SEX, SHELL SIZE 17, CPC					
		3 PLC ± -	APPLICATION SPEC						
		4 PLC ± - ANGLES ± -	_	SIZE	CAGE CODE DRAWING NO		RES	TRICTED TO	
	MATERIAL HOUSING: NYLON, BLACK	FINISH –	WEIGHT	A1	00779 <b>C-</b> 2064	125		_	
SEAL: ELASTOMER, GREY			CUSTOMER DRAWING		SC	ALE 2.1 SHEET 1	1	REV K	

NOTES:

- 1. CAVITY IDENTIFICATION ON FRONT AND REAR FACE.
- 2. WILL ACCEPT (3) TYPE XII SOCKET CONTACTS.
- TE LOGO AND PART NUMBER CAN BE LOCATED ON ANY FLANGE EDGE.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 206425-5