

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4			
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

1/4-36UNS-2A

9.55±0.3
(13.55)

4±0.3

MARKING
HRS

1

2

3 PRESS FITTING

4

5 PRESS FITTING

φ1.27±0.1

5.08±0.05

2.54±0.05

5-φ1.5^{+0.1}₀

2.54±0.05

5.08±0.05

RECOMMENDED PC BOARD
HOLE PATTERN

4.1±0.1

(5.08)

6^{+0.15}_{-0.1}

4.1±0.1

(5.08)

6^{+0.15}_{-0.1}

3	BERYLLIUM COPPER	GOLD PLATING			
2	PTFE		5	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	4	PTFE	
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M.KANEKO	M.KANEKO	K. Shimizu	J. Mitani	
RoHS COMPLIANT	06.12.13	06.12.13	06.12.14	06.12.14	

DRAWING NO.	PART NO.
EDC4-010443-40	HRM-300-134B(40)

SACLE	DRAWING NO.	PART NO.	CODE NO.
5 : 1	EDC4-010443-40	HRM-300-134B(40)	CL323-0296-7-40

UNITS	mm	1	1

FORM NO. 228

