

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

PRICK PUNCH (2 POINTS)

PRESS FITTING

15.63±0.3

9.7^{+0.5}_{-0.3}

13.5±0.5

1/4-36UNS-2A

BRAZING

SOLDERING (PB-FREE)

MARKING

A (2:1)

2.54±0.05

5.08±0.05

2.54±0.05

5.08±0.05

5-ø1.5^{+0.1}₀

RECOMMENDED PC BOARD HOLE PATTERN (2:1)

ø1.27±0.1

4-(□0.95)

6^{+0.15}_{-0.1}

(5.08)

(5.08)

6^{+0.15}_{-0.1}

4

3

2

1

5

6

7

4 PRESS FITTING

4	PTFE		7	BRASS	NICKEL PLATING
3	PTFE		6	BRASS	GOLD PLATING
2	BRASS	NICKEL PLATING	5	BERYLLIUM COPPER	GOLD PLATING
1	STAINLESS STEEL	NICKEL PLATING			
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD) CL	DRAWN Y. Sugi 06.04.26	DESIGNED T. Katayama 06.04.26	CHECKED H. Shimizu 06.04.26	APPROVED I. Mitani 06.04.26	RELEASED
RoHS COMPLIANT					

	DRAWING NO. EDC4-009639-40	PART NO. HRM-300-126S(40)
SCALE 5 : 1		CODE NO. CL323-0253-4-40
UNITS mm		

TO	RF		
----	----	--	--

1

2

3

4

FORM NO. 228