


Technical drawing of a 500-1SV HRM assembly, showing three views: a top view, a side view, and a panel cutout view.

Top View: Shows a circular component with concentric rings. Dimensions include an outer diameter of 10 ± 0.15 HEX and an inner diameter of $7.4^{+0.05}_{-0.15}$.

Side View: Shows the assembly with various components labeled with callouts 1 through 6. Dimensions include a total height of 20.7 ± 0.2 , a section height of 12.5 ± 0.3 , a section height of 6.5 ± 0.3 , a section height of 2.2 ± 0.2 , and a base diameter of $\phi 12.7 \pm 0.3$. Callouts include: 1/4-36UNS-2A, 5/16-32UNEF-2A, MARKING 500-1SV HRM (OPPOSITE SIDE), 500, PRICK PUNCH (2 POINTS), and PRESS FITTING.

Panel Cutout View: Shows a circular cutout with a diameter of $\phi 7.9^{+0.1}_0$ and a height of $7.5^{+0.1}_0$. The text "PANEL CUTOUT" and "PANEL THICKNESS: 1.5 ~ 3.0 mm" is present.

3	BERYLLIUM COPPER	GOLD PLATING		6	BRASS	NICKEL PLATING		
2	PTFE			5	PHOSPHOR BRONZE	NICKEL PLATING		
1	STAINLESS STEEL	PASSIVATE		4	SILICON RUBBER	(RED)		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 4 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : KY. SHIMIZU		15. 10. 07	DRAWING NO. EDC-131565-40-40			
		CHECKED : KY. SHIMIZU		15. 10. 07	PART NO. HRM-500-1SV(40)			
		DESIGNED : TO. KATAYAMA		15. 10. 07	CODE NO. CL323-0659-9-40			
		DRAWN : MH. OGUSHI		15. 10. 07	 1/			