

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4	
A						A	
B						B	
C						C	
D						D	
E						E	
F						F	

Technical drawing of a connector. The top view shows a hexagonal base with a central circular feature. Dimensions include a hex size of 8 ± 0.2, an outer diameter of 6.6 (+0.05/-0.1), and an inner diameter of 3.63 (+0.04/-0.02). Callouts 1, 2, 3, and 4 point to different parts of the connector. A note indicates the connector uses the center conductor of the applicable cable as the center terminal. A detail view shows a 60-degree angle and a 2.3mm dimension.

NOTE 1. THE CONNECTOR USES THE CENTER CONDUCTOR OF THE APPLICABLE CABLE AS THE CENTER TERMINAL.
[APPLICABLE CABLE]
RG-402(0.141 INCH SEMI-RIGID CABLE)

2	BERYLLIUM COPPER	NICKEL PLATING	4	STAINLESS STEEL	PASSIVATE
1	STAINLESS STEEL	GOLD PLATING	3	SILICONE RUBBER	(RED)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 5 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------------	--	----------------	-----------	--------------------------	----------	---------	------

HIROSE ELECTRIC CO., LTD.

APPROVED : NK. NINOMIYA 20220202

CHECKED : NK. NINOMIYA 20220202

DESIGNED : MT. KANEKO 20220201

DRAWN : YK. MITSUISHI 20220201

DRAWING NO. EDC-007291-09-00

PART NO. HRM-101S(09)

CODE NO. CL0323-0153-0-09

1/1

FORM HC0011-5-51

2

3

4